

### PRESS SERIES COLOR PRINTING SYSTEMS simply smarter

# Do more with color and expand your power of expression with industry-leading 6-color printing technology.

The Color Press Series from Sharp delivers unrivaled capabilities to digital printing. With stunning 4-color imaging that can be augmented with printing of up to 6 specialty colors in one pass, the Sharp Color Press Series can make your print jobs virtually come to life. Create a variety of metallic effects with Silver and Gold underlay or add bright Pink for an innovative, eye-catching design.




The BP-1200S Color Press Series shown in a full configuration.

## Unleash your design potential like never before!

#### Superior imaging begins with stunning 4-color quality.

The Color Press Series is built on a proven CMYK system, making it the perfect choice for a broad range of digital jobs. Take on more specialty short runs without compromising.



- High-speed printing up to 120 ppm even when printing in 6 colors.
- Ultra-high output resolution at 2,400 x 2,400 dpi.
- Supports a broad range of paper stock from 52 gsm to 400 gsm.
- Create eye-catching metallic colors with the Color-Logic Metallic Color System™, or add dazzling neon effects with the Touch7 Neon Color System™.
- In-line sensor (ILS) helps ensure precision registration, image stabilization and calibration, all at rated speed.

- Print professional full-bleed documents and banners with versatile finishing options.
- 27" (diagonally measured) high resolution display provides easy operation and offers an engaging user experience.
- Small particle toner delivers smooth reproduction, balanced density and solid color fill.
- Powerful Fiery print server maximizes engine performance with superior image processing.
- Time-saving purge function automatically ejects misfeeds for jam removal that is virtually hands-free.

- Maximum paper capacity 13,250 sheets.
- Specialty toner can be layered together or combined with CMYK to create stunning spot colors and metallic effects.
- Built-in cooling module cools printed output during operation, to ensure proper finishing and stacking.
- Specialty toner cartridges can be easily swapped out enabling fast changeovers for custom jobs with virtually zero waste.
- ENERGY STAR® 3.2 certified. Imaging products meeting this standard help contribute to a cleaner environment.

## SPECIFICATIONS BP-1200C/1200S

Main Specifications	1
BP-1200C/1200S	Base models include 4,200 sheet paper capacity (2,100
	sheets x 2 drawers). The BP-1200S is a 6-color printing
	system and the BP-1200C is a 4-color printing system,
	upgradable to 6-color.
Туре	Full color, production printing system
User Interface	27" (diagonally measured) high resolution display with
	keyboard and mouse
Color Print Engine	BP-1200C is a 4-color system, upgradable to a 6-color
	system with options. BP-1200S is a 6-color system.
Print Speed	120 pages per minute (letter), 60 pages per minute (ledger).
Output System	Dry electrostatic transfer, dual component developing system.
Print Resolution	2,400 x 2,400 dpi
Paper Sizes	Max: 12.6" x 19.2", Min: 4.1" x 5.8"
Paper Weight	52 to 400 gsm (long paper 82 to 300 gsm is available as
Danas Food Custom	an option)
Paper Feed System	Standard: 4,200 sheets (2,100 sheets x 2 drawers) Optional: 250-sheet Multi Bypass Trays + 2,100-sheet x 2
	drawer High-Capacity Feeder + tandem 2,100-sheet x 2
	drawer High-Capacity Feeder, or 2,200-sheet x 2 drawer Air
	Suction Feeder + 250-sheet multi bypass trays + chained
	2,200 sheet x 2 drawer Air Suction Feeder, or 2,200-sheet
	Air Suction Feeder + 900-sheet Banner Unit + chained
	2,200-sheet Air Suction Feeder
Maximum Paper	13,250 sheets with options
Capacity	10,200 onotio war options
Output Paper	500 sheets (standard)
Capacity	ood onoote (ottainatala)
	200-240 VAC , 44A, 60 Hz
Power Consumption	
	Main Unit: 118" (W) x 44" (D) x 71" (H)
Weight (Approx.)	3,439 lbs.
Print Controller	
Fiery Print Server	Based on Fiery FS400 Pro Platform
Туре	External
CPU	Intel® Xeon® Dual 12 Core Processor
Memory	32 GB (max)
	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two
Memory Storage Devices	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives
Memory Storage Devices Server Operating	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two
Memory Storage Devices Server Operating System	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC
Memory Storage Devices Server Operating System Printer Description	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives
Memory Storage Devices Server Operating System Printer Description Language	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC  Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC  Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF  DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP,
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC  Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF  DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SMMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF),
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port-
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port-based access control, 802.1x authentication, USB security
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SMMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking,
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port-based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T (10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SMMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.)	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features  Power Requirements Power Consumption Dimensions (Approx.)  High Capacity Feeder Paper Size (Feeder	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  Pers (BP-PT17/BP-PT18) 13" x 19.2" (Max), 4.1" x 5.8" (Min)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feeder Apper Size (Feeder or Bypass Tray)	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  **StB-P-P11/BP-P118) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2"
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed Paper Size (Feeder Reypass Tray) Paper Weight	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPY6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  218 CBP-P117/BP-P118) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feeder Apper Size (Feeder or Bypass Tray)	32 GB (max)  SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC  Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF  DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T  USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates.  100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  218 CBP-PT17/BP-PT18)  13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feeder or Bypass Tray) Paper Weight Paper Capacity	32 GB (max) SSD boot drive 480 GB for OS and Fiery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SMMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  sets (BP-PT17/BP-PT18) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed Paper Size (Feeder Reypass Tray) Paper Weight	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  21" X 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass) BP-PT17: 100-120 VAC, 6A, 60 Hz
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed Paper Size (Feeder ro Bypass Tray) Paper Weight Paper Capacity Power Source	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPY6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  **S** (BP-P117/BP-P118) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-P117: 100-120 VAC, 6A, 60 Hz BP-PT18: 100-120 VAC, 6A, 60 Hz
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed Paper Size (Feeder ro Bypass Tray) Paper Weight Paper Capacity Power Source	32 GB (max)  SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC  Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF  DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T  USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, Apple Talk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates.  100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  278 (BP-PT17/BP-PT18)  13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass) BP-PT17: 100-120 VAC, 6A, 60 Hz BP-PT17: 880 W (Max) BP-PT17: 880 W (Max)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feeder Or Bypass Tray) Paper Weight Paper Capacity Power Source Power Consumption	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  278 (BP-PT17/BP-PT18) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass) BP-PT17: 100-120 VAC, 6A, 60 Hz BP-PT18: 600 W (Max) BP-PT18: 660 W (Max) BP-PT18: 660 W (Max)
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features Power Requirements Power Consumption Dimensions (Approx.) High Capacity Feed Paper Size (Feeder ro Bypass Tray) Paper Weight Paper Capacity Power Source	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders) Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  21" X 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass) BP-PT17: 100-120 VAC, 6A, 60 Hz BP-PT18: 100-120 VAC, 5A, 60 Hz BP-PT18: 100-120 VAC, 5A, 60 Hz BP-PT17: 466 lbs.
Memory Storage Devices Server Operating System Printer Description Language Microsoft Office Formats Interface Network Protocols Security Features  Power Requirements Power Consumption Dimensions (Approx.)  High Capacity Feeder Paper Size (Feeder or Bypass Tray) Paper Weight Paper Capacity Power Source Power Consumption Weight (Approx.)	32 GB (max) SSD boot drive 480 GB for OS and Flery software + two 2-TB Hard Disk Drives Microsoft® Windows 10 IoT Enterprise 2019 LTSC Adobe PostScript 3, PDF/X-1a, 3, and 4; EPS; JPEG; TIFF DOC, DOCX, XLS, XLSX, PPT, PPTX, PUB (via hot folders)  Ethernet: 1000 Base-T/100 Base-T/10 Base-T USB 3.0 Ports: four on rear, three on Fiery QuickTouch panel TCP/IP, AppleTalk, bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPV6 support, LDAP authentication Secure Erase, Security Profiles, User Data Encryption, Port- based access control, 802.1x authentication, USB security prevents connecting external storage devices, Port Blocking, IP Filtering, IPsec, HTTPS, TLS1.3, Secure Printing, Digitally signed software updates. 100-240 VAC (auto switching), 50/60 Hz, 6A 600 W (Max) 9.25" (W) x 22.5" (D) x 20.75" (H)  278 (BP-PT17/BP-PT18) 13" x 19.2" (Max), 4.1" x 5.8" (Min) Custom Size: 3.86" x 5.83" to 13" x 19.2" 52-350 gsm (Feeder) 2,100 sheets x 2 drawers (Feeder) BP-PT17: 250 sheets (Bypass) BP-PT17: 100-120 VAC, 6A, 60 Hz BP-PT18: 600 W (Max) BP-PT18: 660 W (Max) BP-PT18: 660 W (Max)

Air Suction Feeders	(BP-PT12/BP-PT13) and Banner Unit (BP-PT22)
Paper Size	13" x 19.2" (Max), 4.1" x 5.8" (Min)
	BP-PT12 Custom Size: 3.8" x 5.8" to 13" x 19.2",
	BP-PT13 + BP-PT22 Custom Size: 8.3" x 8.3" to 13" x 47.2"
Paper Weight	(Upper Tray), 3.8" x 5.8" to 13" x 19.2" (Lower Tray) 52-400 gsm
Paper Capacity	2,200 sheets x 2-tray + 250 sheets
.,,	(+ 900 sheets BP-PT13 + BP-PT22)
Power Source	100-120 VAC, 6A
Power Consumption	
Weight (Approx.)	BP-PT12: 428 lbs., BP-PT13 + BP-PT22: 470 lbs.
Dimensions (Approx.)	) BP-PT12: 39" (W) x 30" (D) x 39" (H) BP-PT13 + BP-PT22: 62.2" (W) x 30" (D) x 39" (H)
	BF-F113 + BF-F122. 02.2 (W) X 30 (D) X 39 (N)
Tandem Air Suction	Feeders (BP-PT14/BP-PT15/BP-PT16)
and Banner Unit (Bl	
Paper Size	13" x 19.2" (Max), 4.1" x 5.8" (Min)
	BP-PT14 + BP-PT15 custom size: 3.8" x 5.8" to 13" x 19.2"
	BP-PT14 + BP-PT16 + BP-PT22 custom size: 3.8" x 5.8" to 13" x 19.2", 8.3" x 8.3" to 13" x 47.2" (Upper tray)
Paper Weight	52-400 gsm
Paper Capacity	BP-PT14 + BP-PT15 2,200 sheets x 2-tray x 2 feeder units +
	250 sheets BP-PT14 + BP-PT16 + BP-PT22: 2,200 sheets x
	2-tray x 2 feeder units + 250 sheets + 900 sheets
Power Source	100-120 VAC, 6A, 60Hz x 2 power connections
	880 W x 2 feeder units (Max)
Weight (Approx.)	BP-PT14 + BP-PT16 + BP-PT22: 926 lbs.
Di	BP-PT14 + BP-PT15: 888 lbs.
Dimensions (Approx.	) BP-PT14 + BP-PT15: 78" (W) x 30" (D) x 39" (H) BP-PT14 + BP-PT16 + BP-PT22: 101.2" (W) x 30" (D) x 39" (H)
	BI 1114   BI 1110   BI 1122. 101.2 (W) x 60 (B) x 60 (H)
Finisher (BP-PP23)/	Finisher with Booklet Maker (BP-PP24)
Туре	BP-PP23 & BP-PP24: Output Tray- Sort/Stack, Finishing
	Tray-Sort/Stack, BP-PP24: Booklet Tray- Sort/Stack
Paper Size	Output Tray: (Max) 12.6" x 19.2", (Min) 4.1" x 5.8"
	Finishing Tray: (Max) 12.6" x 19.2", (Min) 5.8" x 8.3"
	Output Tray Custom Size: 3.8" x 5.8" to 13" x 47.2" Finishing Tray Custom Size: 5.8" x 5.8" to 13" x 19.2"
Paper Weight	Output Tray: 52 to 400 gsm. Finishing Tray: 52 to 350 gsm.
Paper Capacity	BP-PP23: 3,000 sheets not stapled (letter size)/200 sets stapled
	BP-PP24: 2,000 sheets not stapled (letter size) or 200 sets
	stapled, up to 2,000 sheets. Booklet tray 20 sets
	Output Tray: 500 sheets (letter size)
Staple	100 sheets (up to 90 gsm)
Punch Booklet Finishing	2-hole / 3-hole punch BP-PP24 only: Saddle Staple: 30 sheets, Single Fold: 5 sheets
Power Source	100-127 VAC, 3A, 60 Hz
Power Consumption	
Weight (Approx.)	BP-PP23: 180lbs. / BP-PP24: 225lbs.
Dimensions (Approx.)	) BP-PP23: 33.6" (W) x 28.5" (D) x 47.4" (H)
	With Folder Unit: 43" (W) x 28.5" (D) x 47.4" (H)
	BP-PP24: With Folder Unit: 44.4" (W) x 28.5" (D) x 47.4" (H)
Folder Unit (BP-PP2	2)
Paper Size	Z Fold Half Sheet 11" x 17", Tri Fold 8.5" x 11"
Paper Weight	60-90gsm
Paper Capacity	Tri fold- 30 sheets
Power Source	100-127 VAC, 1A, 60Hz
Power Consumption	
Weight (Approx.)	106 lbs.
vimensions (Approx.	) 9.1" (W) x 28.5" (D) x 39" (H)
High Capacity Stack	ker (BP-PP17)
Paper Capacity	Output Tray- 500 sheets, Stacker- 5,000 sheets
Paper Size	Output Tray- (Max) 12.6" x 19.2", (Min) 4.1" x 5.8"
	Custom Size: 3.8" x 5.8" to 13" x 19.2"
	High Capacity Stacker- (Max) 12.6" x 19.2", (Min) 7.2" x 10.1"
	Custom Size: 8" x 7.1" to 13" x 19.2"
Paper Weight	Output Tray- 52-400 gsm, Stacker- 52-300 gsm
Power Source Power Consumption	100-120 VAC, 60Hz
Weight (Approx.)	342 lbs.
	31 E" (M) v 20 E" (D) v 41" (U)

BP-PE12	Fiery Controller, Workstation, Spectrophotometer, Impose,
	Compose, Graphics Arts Package, Monitor, Keyboard
	and Mouse
BP-PW21	Fiery Specialty Color License Kit (for 5th and 6th colors)
BP-PT12	Air Suction Feeder
BP-PT13	Air Suction Feeder for Banner Unit
BP-PT14	Chained Air Suction Feeder (R)
BP-PT15	Chained Air Suction Feeder (L)
BP-PT16	Chained Air Suction Feeder for Banner Unit
BP-PP10	Offset Catch Tray
BP-PP11	Long Catch Tray
BP-PP12	Catch Tray Enabling Kit
BP-PP13	Interface Decurler Module
BP-PP14	Inserter
BP-PP15	Static Eliminator
BP-PP16	Static Eliminator Corotron
BP-PP17	High Capacity Stacker
BP-PP18	Stacker Paper Cart
BP-PP19	Accessibility Kit for High Capacity Stacker
BP-PP20	Top Tray Extension Kit for High Capacity Stacker
BP-PP21	Crease/Two-sided Trimmer
BP-PP22	Folding Unit
BP-PP23	Finisher
BP-PP24	Finisher with Booklet Maker
BP-PP25	Punch Module
BP-PP26	Stacking Guide for Output Tray
BP-PP27	Finisher Tray Extension Kit
BP-PP28	Banner Print Extension Kit
BP-PP29	Square Back Fold Trimmer
BP-PT10	Multi Bypass Tray
BP-PT11	Multi Bypass Tray for Banner Print
BP-PT17	High Capacity Feeder
BP-PT18	Second High Capacity Feeder
BP-PT19	Connection Module
BP-PT20	
	Docking Bracket Kit (for Air Suction Feeder)
BP-PT21	Position Adjuster
BP-PT22	Banner Unit for Air Suction Feeder
BP-PT23	Post Card Kit for Air Suction Feeder
BP-PT24	Post Card Kit for High Capacity Feeder
BP-PT25	Banner Feed Guide
BP-PT26	Banner Feeder Extension Kit
BP-PS14	Staple Cartridge
MX-SCX1	Staple Cartridge (For Saddle Stitching)
BP-PM11	Specialty Color Extension Kit
BP-PM12	Specialty Color Engine Kit (Overlay)
BP-PM13	Specialty Color Engine Kit (Underlay)
BP-PM14	Marking Module Kit
BP-PM15	White Marking Module Kit
BP-PM24	Media Expansion Kit
BP-PM16	Toner Enabling Kit (Clear)
BP-PM17	Toner Enabling Kit (Gold)
BP-PM18	Toner Enabling Kit (Gold)
BP-PM19	Toner Enabling Kit (Silver)  Toner Enabling Kit (Pink)
BP-PM20	Toner Enabling Kit (Firik)  Toner Enabling Kit (Textured Paper)
BP-PM21	Toner Enabling Kit (White)
BP-PM22	Starter Kit for Specialty Toner Exchange
BP-PM23	Storage Box for Specialty Toner
Supplies <sup>1</sup>	
BP-NT120BA	Toner Cartridge (Black)
BP-NT120CA	Toner Cartridge (Cyan)
BP-NT120MA	Toner Cartridge (Magenta)
BP-NT120YA	Toner Cartridge (Yellow)
BP-NT120LA	Toner Cartridge (Clear)
BP-NT120GA	Toner Cartridge (Gold)
BP-NT120SA	Toner Cartridge (Silver)
BP-NT120WA	
BP-NT120WA BP-NT120TA	Toner Cartridge (White)
BP-NT120WA BP-NT120TA BP-NT120PA	

Fiery Controller, Workstation, Spectrophotometer, Impose,

Optional Equipment BP-PE12



SHARP ELECTRONICS CORPORATION 100 Paragon Drive, Montvale, NJ 07645 1-800-BE-SHARP • www.sharpusa.com

Dimensions (Approx.) 31.5" (W) x 28.5" (D) x 41" (H)

Design and specifications subject to change without notice.

Toner Collection Container Unit

<sup>1</sup> Some features require optional equipment and or supplies. See your local dealer.











Drum unit

BP-DU120

BP-PS11



©2024 Sharp Electronics Corporation. All rights reserved. Sharp, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Microsoft, Excel, PowerPoint, Windows, and Windows Server are trademarks of the Microsoft group of companies. Adobe and PostScript are trademarks or registered trademarks of Adobe in the US and/or other countries. Fiery is a trademark or registered trademark of Fiery, LLC. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners. Images shown are for illustration purposes only.